

ADAM-4016

ADAM-4017

1-ch Analog Input/Output Module

8-ch Analog Input Module



ADAM-4016



ADAM-4017



Specifications

General

- **Connectors** 2 x plug-in terminal blocks (#14 ~ 22 AWG)
- **Power Consumption** 2.2 W @ 24 V_{DC}
- **Watchdog Timer** System (1.6 s)
- **Supported Protocols** ASCII command

Analog Input

- **Channels** 1 differential
- **Input Impedance** Voltage: 2 MΩ
- **Input Type** Current: 125 Ω (Added by users)
- **Input Range** mV, mA
- **Input Range** ±15 mV, ±50 mV, ±100 mV, ±500 mV, ±20 mA

Analog Output

- **Channels** 1
- **Accuracy** 0.05% of FSR
- **Output Type** V
- **Output Range** 0 ~ 10 V
- **Drift** ±50 ppm/°C
- **Drive Current** 30 mA
- **Isolation Voltage** 3,000 V_{DC}

Digital Output

- **Channels** 4, open collector to 30 V, 30 mA max. load
- **Power Dissipation** 300 mW

Common Specifications

General

- **Power Input** Unregulated 10 ~ 30 V_{DC}
- **Connectors** 2 x plug-in terminal block (#14 ~ 22 AWG)

Analog Input

- **Accuracy** Voltage mode: ±0.1% or better
- **Resolution** Current mode: ±0.2% or better
- **Resolution** 16-bit

Sampling Rate

10 sample/second (total)

Isolation Voltage

3,000 V_{DC}

CMR @ 50/60 Hz

120 dB

NMR @ 50/60 Hz

100 dB

Span Drift

±25 ppm/°C

Zero Drift

±6 μV/°C

Environment

▪ Humidity

5 ~ 95% RH

▪ Operating Temp.

-10 ~ 70°C (14 ~ 158°F)

▪ Storage Temp.

-25 ~ 85°C (-13 ~ 185°F)

Ordering Information

▪ ADAM-4016

1-ch Analog Input/
Output Module

▪ ADAM-4017

8-ch Analog Input
Module

1
Motion Control

2
Hazardous Location

3
Energy Automation

4
Building Automation Systems

5
Automation Software

6
Operator Panels

7
Automation Panel PCs

8
Industrial Monitors

9
Industrial Ethernet

10
Device Servers & Gateways

11
Serial Communication Cards

12
Embedded Auto. Computers

13
PACs

14
M2M I/O

15
Distributed Nano Controllers

16
RS-485 I/O

17
Ethernet I/O

18
DAQ Boards