IPC-3026

Quiet Compact Chassis for Half-size SHB/SBC



Features

- Supports 6-slot PICMG 1.3/1.0 backplane
- Shockproof drive bay for one 3.5" HDD
- Supports two 2.5" HDDs by hot-swap tray
- LED indicators for system fault detection
- Lockable front door prevents unauthorized access
- Built-in Intelligent System Module enabling whole system fan control and remote manageability

Quiet Specifications

C € FCC

Diele Drive Deve		External	Internal			
Disk Drive Bay	3.5"	1	-			
Cooling	Fan	1 (9 cm 44.6 CFM)				
	Air Filters	Yes				
I/O Interface	USB	2 (Front accessible)				
Miscellaneous	LED Indicators	Power, HDD, Temp, Fan				
	Front Panel	Reset button, Power switch				
	Rear Panel	Reserved four 9-pin D-Sub openings, 25-pin opening,	DVI opening, dual USB ports			
Intelligent System Module Remote Monitoring	CPU/System fan speed , CPU/System temperature , motherboard voltage					
	(Only selected Advantech MBs/CPU cards with WISE-PaaS/RMM installed can fully enable these functions, check with Advantech local rep. for detailed					
	information.)					
Environment		Operating	Non-operating			
	Temperature	0 ~ 40 °C (32 ~ 104 °F)	-20 ~ 60 °C (-4 ~ 140 °F)			
	Humidity	10 ~ 85% @ 40 °C, non-condensing	10 ~ 95% @ 40 °C, non-condensing			
	Vibration (5-500 Hz)	1 Grms	2 G			
	Shock	10 G (with 11 ms duration, half sine wave)				
Physical Characteristics	Dimensions (W x H x D)	150 x 222 x 270 mm (5.9" x 8.74" x 10.63")				
	Weight	4.4 kg (9.7 lb)				

Front View



Note: Hot swap drive bay module should be bought separately.



Rear View



All product specifications are subject to change without notice.

IPC-3026



Ordering Information

Part Number	Power Supply	Wattage	Туре	Input
IPC-3026BP-15ZE	96PS-A150WFX-1	150W	Single	AC 100 ~ 240 V (full range)

Optional Accessories

Ordering P/N	Description
IPC-DT-3120E	Mobile rack for dual 2.5" SATA HDDs with a 3.5" drive bay occupancy

Backplane Options

-	-							
-	-							
		-	-	-	1			
4	-	-	-	1				
PICMG 1.3								
-	1	-	1	-	1			
-	1	-	-	4	1			
2	1	-	-	2	1			
3	1	-	-	1	1			
	- - 2	- 1 - 1 2 1	- 1 - - 1 - 2 1 -	- 1 - 1 - 1 2 1	- 1 - 1 - - 1 - 4 2 1 2			