PCIE-1680 PCI-1680U

2-Port CAN Bus PCIE Card with Isolation Protection

2-Port CAN Bus Universal PCI Card with **Isolation Protection**



Features

- PCIe bus specification 1.1 compliant
- 2 x Independent CAN ports
- Up to 1 Mbps transmission speeds
- 16 MHz CAN controller frequency
- Optical isolation protection of 2,500 VDC
- I/O address automatically assigned by PCI PnP
- Transmit/Receive status LED indicators •
- Windows DLL library and examples included •
- Supports Windows CE5/CE6/XP/7/8.1/10 drivers and utilities
- Supports Linux 2.4.xx/2.6.xx, QNX 6.5, and Intel[®] x86 architecture

Introduction

PCI-1680 and PCIE-1680 are purpose-built communication cards that ensure CAN connectivity. With 2 independent CAN controllers built in, PCI-1680 and PCIE-1680 enable bus arbitration and error detection with automatic transmission repetition, drastically reducing data loss and ensuring system reliability. Additionally, both PCI-1680 and PCIE-1680 operate at baud rates of up to 1 Mbps.

Specifications

General

- Bus Type Certification Connectors
- PCI Express V1.0/Universal PCI CE, FCC
- 2 x DB9, male
- 2 x 10 pin box wafer (optional)
- Ports
- 2 - Power Consumption 3.3 V @ 600 mA (typical)

Communication

- NXP SJA-1000 CAN Controller
- CAN Transceiver
- CAN H, CAN L Signal Support CAN 2.0 A/B
- Protocol
- Data Transfer Rate Programmable up to 1 Mbps

16MHz

CAN Frequency

Protection

Isolation Protection 2,500 V_{DC}

Mechanical and Environmental

- Operating Temperature 0 ~ 70 °C (32 ~ 158 °F) (refer to IEC 60068-2-1, 2)
- Storage Temperature -40 ~ 85 °C (-40 ~ 185 °F)
- Operating Humidity 5 ~ 95% relative humidity, non-condensing
- Dimensions (L x H) 168 x 111 mm (6.6" x 4.4")

Ordering Information

- PCIE-1680-AE
- PCI-1680U-BE

Accessories

OPT1-DB9E-AE

DB9 to 10-pin wiring board

2-port CAN bus PCIE card with isolation protection

2-port CAN bus PCI card with isolation protection

AD\ANTECH Industrial I/O

All product specifications are subject to change without notice.

NXP TJA1051T